Triskel - Specifications

Computer and case

Screen	17"W LCD TFT
Inputs	Detachable keyboard with 108 keys and integrated touchpad
Network	RJ45, GB Lan
Power supply	650 W Auto Switch (90V - 240V)
CPU / Memory	i7 975, 3.33 GHz / 4 GB
VGA	nVidia FX3800
HDD	2TB HDD
DVD	Slim
USB	6
OS	Windows 7 Professional
Speakers	2x6 Watt
Size	W/H/D 440 mm x 310 mm x 225 mm
Weight	~15 kg
Transport	Included rolling suitcase with telescopic handle

Audio capture

You may capture up to 4 synchronised audio channels

Klewel Analog	**Klewel Digital**
4 x unbalanced RCA (stereo) via included breakout cable	On request

Video capture

Video format: NTSC/PAL

| **Klewel Analog**	**Klewel Digital**
1x composite video via included BNC/RCA adapter	On request

VGA/DVI capture

The system captures everything that is shown by the presenter to the audience (presentations, videos, websites, demos, …) using either Analog (VGA) or Digital (DVI) input.

DVI up to 1920 x 1200
RGB/VGA up to 2048 x 1536
HDMI up to 1080p
Automatic slide detection and videos/animations capture

Publishing

Once captured, data is uploaded to our cloud-based servers for processing. Editing is performed online using our easy-to-use web platform. The presentations are then accessible via Internet on desktop and mobile devices.

Upload	Via Ethernet connection (no connection required during capture)
Indexing	OCR-based slide indexing enabling browse & search
Processing	State of the art multimedia encoding
Editing	Via Klewel online portal
Streaming	Via industry leading Content Delivery Network (CDN)
Online access	Via Internet on computers and/or mobile devices (browse & search)
Offline access	Adobe Flash™ based DVD can be created (browse & search)
Web integration	Copy/paste (embed code) in any webpage

Hardware warranty

1 year limited hardware warranty

Visit us on the web at www.klewel.com